

J308 – J310 / SST308 – SST310


FEATURES

- Industry Standard Part in Low Cost Plastic Package
- High Power Gain
- Low Noise
- Dynamic Range Greater Than 100dB
- Easily Matched to 75Ω Input


APPLICATIONS

- VHF/UHF Amplifiers
- Oscillators
- Mixers

PIN CONFIGURATION



TO-92



SOT-23

5021

PRODUCT MARKING (SOT-23)

SST308	Z08
SST309	Z09
SST310	Z10

ABSOLUTE MAXIMUM RATINGS

(T_A = 25°C unless otherwise specified)

Drain-Gate Voltage	-25V
Drain-Source Voltage	-25V
Continuous Forward Gate Current	-10mA
Storage Temperature Range	-55°C to +150°C
Operating Temperature Range	-55°C to +135°C
Lead Temperature (Soldering, 10sec)	+300°C
Power Dissipation	360mW
Derate above 25°C	3.27mW/°C

NOTE: Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions above those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ORDERING INFORMATION

Part	Package	Temperature Range
------	---------	-------------------

J308-310	Plastic TO-92	-55°C to +135°C
SST308-310	Plastic SOT-23	-55°C to +135°C

For Sorted Chips in Carriers see U308 series.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise specified)

SYMBOL	PARAMETER	308			309			310			UNITS	TEST CONDITIONS	
		MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX			
BV _{GSS}	Gate-Source Breakdown Voltage	-25			-25			-25			V	I _G = -1μA, V _{DS} = 0	
I _{GSS}	Gate Reverse Current			-1.0			-1.0			-1.0	nA	V _{GS} = -15V, V _{DS} = 0	
				-1.0			-1.0			-1.0	μA		T _A = 125°
V _{GS(off)}	Gate-Source Cutoff Voltage	-1.0		-6.5	-1.0		-4.0	-2.0		-6.5	V	V _{DS} = 10V, I _D = 1nA	
I _{DSS}	Saturation Drain Current (Note 1)	12		60	12		30	24		60	mA	V _{DS} = 10V, V _{GS} = 0	
V _{GS(f)}	Gate-Source Forward Voltage			1.0			1.0			1.0	V	V _{DS} = 0, I _G = 1mA	
g _{fs}	Common-Source Forward Transconductance	8,000	17,000		10,000	17,000		8,000	17,000		μS	V _{DS} = 10V I _D = 10mA (Note 2)	f = 1kHz
g _{os}	Common-Source Output Conductance			250			250			250			
g _{fg}	Common-Gate Forward Transconductance		13,000			13,000			12,000				
g _{og}	Common Gate Output Conductance		150			150			150				

ELECTRICAL CHARACTERISTICS (Continued) (T_A = 25°C unless otherwise specified)

SYMBOL	PARAMETER	308			309			310			UNITS	TEST CONDITIONS	
		MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX			
C _{gd}	Gate-Drain Capacitance		1.8	2.5		1.8	2.5		1.8	2.5	pF	V _{DS} = 10V, V _{GS} = -10	f = 1MHz (Note 2)
C _{gs}	Gate-Source Capacitance		4.3	5.0		4.3	5.0		4.3	5.0			
e _n	Equivalent Short-Circuit Input Noise Voltage		10			10					nV	V _{DS} = 10V, I _D = 10mA	f = 100Hz (Note 2)
Re(v _{fs})	Common-Source Forward Transconductance		12			12			12		μS	V _{DS} = 10V, I _D = 10mA (Note 2)	f = 105MHz
Re(v _{fg})	Common-Gate Input Conductance		14			14			14				
Re(v _{is})	Common-Source Input Conductance		0.4			0.4			0.4				
Re(v _{os})	Common-Source Output Conductance		0.15			0.15			0.15				
G _{pg}	Common-Gate Power Gain at Noise Match		16			16			16		dB	f = 450MHz	
NF	Noise Figure		1.5			1.5			1.5				
G _{pg}	Common-Gate Power Gain at Noise Match		11			11			11				
NF	Noise Figure		2.7			2.7			2.7				

- NOTES:** 1. Pulse test PW 300μs, duty cycle ≤3%.
 2. For design reference only, not 100% tested.